

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	Ø RIGID SPIRAL (AXB IF OVAL)	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH
inch	mm	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm	mm		m
	18	26.2	1.2	4.1	200	18	-	-	5	3.3	7.2	right	50
	20	26	0.9	3	170	20	-	-	5	2.8	6.5	right	50
1	25	30.6	0.7	2.8	185	25	-	-	5	2.7	7.2	right	50
	30	35.6	0.7	2.8	225	30	-	-	5	2.7	7.5	right	50
1 1/4	32	38.2	0.8	3.1	255	32	-	-	5	2.8	8.3	right	50
	35	41.4	0.8	3.2	300	35	-	-	5	3	8	right	50
1 1/2	38	44.4	0.8	3.2	310	38	-	-	5	3	8	right	50
	40	46.6	0.9	3.3	330	40	-	-	4	3.1	8.5	right	50
1 3/4	45	51.6	0.9	3.3	370	45	-	-	4	3.2	9.5	right	50
2	50	57.4	1	3.7	440	50	-	-	4	3.6	10	right	50
	60	68	1	4	560	60	-	-	4	3.9	12	right	50
2 1/2	63	71.5	1	4	600	63.5	-	-	4	3.9	10.8	right	50
	70	78.2	1	4.1	640	70	-	-	4	4	11.5	right	50
	75	84.4	1.1	4.7	730	75	-	-	4	4.5	13.5	right	50
3	76	80.9	1.1	4.7	730	76	-	-	4	4.5	13	right	50
	80	89.6	1.1	4.7	790	80	-	-	4	4.5	14	right	30
3 1/2	90	100.2	1.1	5.1	950	90	-	-	4	4.8	14	right	30
	100	109.4	1	4.7	980	100	-	-	4	4.5	14	right	30
4	102	111	1	4.7	980	101	-	-	4	4.5	14	right	30
	110	120	1.2	5	1120	110	-	-	4	5	15.3	right	30
	120	131	1.3	5.5	1300	120	-	-	4	5	17	right	30